

**OUTLET DEVICE FOR CHOCOLATES AND THE LIKE****TECHNICAL FIELD**

- 5 The present invention relates to technical field of automatic packaging machines, and particularly the invention relates to an outlet device for chocolates or the like for a wrapping machine.

**BACKGROUND ART**

10

In the known wrapping machines, the outlet device provides to carry the products, either partially or completely wrapped, from the folding stations to the outlet area, for in-line connection to a subsequent packaging machine or collection within suitable containers.

- 15 In the case of products having the shape of a solid of revolution, such as small eggs or spheres, depending on the type of wrap to be manufactured, for example "rolled design", with single-, double-end fantail twist, a specific outlet unit is required to be assembled on the wrapping machine respectively capable of carrying the products to the outlet in an ordinate manner while rolling them to complete the wrap thereof with a fancy design, and moving them simply to the outlet according to the so-called "in bulk"
- 20 mode.

- The drawback with these known wrapping machines is that the assembly of the suitable outlet device for manufacturing a particular wrap type is complicated, and this entails both an increase in the machine downtime and the interruption of the production process, as well as having to resort to skilled labour required to carry out these
- 25 expensive operations.

- Packaging machines are known in which two separate and different outlet devices are provided, which are located in two different positions and operated separately, based on the type of wrap of the product. Due to the simultaneous presence of both devices, the outlet device does not require to be replaced each time the type of wrap is changed,
- 30 however separate motors are required, with a consequent larger machine size, more complicated construction and hence an increase in the machine total costs.

**DISCLOSURE OF THE INVENTION**

An object of the present invention is to provide an outlet device being capable of moving the products and providing both an outlet of the so-called "in bulk" type, and an outlet with design rolling, requiring only minimum, quick and easy adjustments.

- 5 Another object is to provide an outlet device capable of operating at high speed with reliable and regular operation, and which is compact and small-sized.

The above objects are achieved in accordance with the claims.

### BRIEF DESCRIPTION OF THE DRAWINGS

10

The characteristics of the present invention are set forth below particularly with reference to the annexed drawings, in which:

- Figure 1 shows a front view of the outlet device being the object of the present invention when associated to moving means of a wrapping machine;
- 15 - Figure 2 shows a sectional view of the device taken along the line II-II from Figure 1;
- Figure 3 shows a plan partial view of the device from Figure 1.

### BEST MODE OF CARRYING OUT THE INVENTION

20

With reference to the Figure 1 to 3, with 1 there is indicated an outlet device for chocolates and the like 100, for a wrapping machine 50 being provided with moving means 51 for each product 100 through a plurality of wrap folding stations.

- The device 1 substantially comprises first 2 and second 3 belt means, which are driven
- 25 by actuating means 10 through first 5 and second 6 connecting means, respectively, to carry the products 100 being taken from the moving means 51 by means of extraction means 15.

- According to a first direction A of the rotary motion of the actuating means 10 the first connecting means 5 connect said actuating means 10 to the first belt means 2, which are
- 30 then capable to move the products 100 along rolling means 4, such as to carry out a wrap of said products 100 according to a so-called "rolled design" shape.

According to the second direction B of rotation of the actuating means 10, the second belt means 3 connect said actuating means 10 to the second belt means 3 moving the

products 100 which do not require to be rolled according to a so-called "in bulk" mode. The first 2 and second 3 belt means are placed one above the other and the rolling means 4 are detachably interposed therebetween.

5 The rolling means 4 essentially consist of a prismatic guide provided with an elongated concave housing 8 complementary shaped relative to the products 100 where the product 100 are rolled thereto from the first belt means 2 for the rolling to be carried out thereon. The shape of the concave housing 8 is related to the shape and size of the product 100 to be wrapped.

10 The position of the rolling means 4 can be adjusted and they can be easily dismounted for quick replacement.

The first belt means 2 preferably consist of a endless timing belt being coated on the outside with a layer of elastic material 13, which abuts and conforms to the surface of product 100 without causing damage thereto.

15 The second belt means 3 consist of one or several endless flat belts set to the proper tensioning level by adjustment through idler rolls 20.

The first 5 and second 6 connecting means are connected to the actuating means 10, consisting of an electric motor through driving means 7 consisting of a closed loop flexible element or a gear chain.

20 The first 5 and second 6 connecting means comprise respective idle wheels of the known type, gripping in the first A and second B directions of rotation of the actuating means, respectively, to impart the motion to the respective first 2 and second 3 belt means.

25 Alternatively, the connecting means 5, 6 can be of the electromagnetic type, operated by the supplying means of the actuating means 10 and electrically/electronically controlled in order to impart or not the rotary motion to the corresponding belt means 2, 3.

The extraction means 15 substantially comprise a pusher 16 being provided with a shaped housing for the product 100 and operated by operating means 17, which provides to take each single product 100 from the moving means 51 and carry it to the first 2 or second 3 belt means.

30 The operating means 17 consist, in the preferred embodiment, of a couple of levers 18, 19, one of which being motor-driven, which are connected to the pusher 16 to form a articulated quadrilateral. The oscillation set on one of the levers defines the reciprocating movement parallel to the belt means 2, 3 of pusher 16.

There are provided electronic calculation and control means being generally integrated to those in the wrapping machine to which the device is assembled, which are suitable to control the phase relationship of the extraction means 15 to the moving means 51.

5 The operation of the outlet device 1 for chocolates and the like 100 provides the separate and alternate operation of the first 2 and second 3 belt means by selecting the direction of rotation of the actuating means 10.

The rotation of the actuating means 10 according to a first direction A, for example counter-clockwise such as illustrated in Figure 1, defines the insertion of the first connecting means 5 and the removal of the second connecting means 6. In the particular  
10 case, the idle wheel of the first connecting means 5 imparts the motion to the first belt means 2, while the idle wheel of the second connecting means 6 turns "idle" thus leaving the second belt means 3 stationary. Thereby, the products 100 to be rolled, being taken through the extraction means 15 from the moving means 51 of the wrapping machine 50, can be moved along the elongated concave housing 8 of the rolling means  
15 4, in order to carry out a wrap with a so-called "rolled design" shape.

On the contrary, a rotation of the actuating means 10 in the opposite direction B, defines the insertion of the second driving means 6 and the removal of the first driving means 5, consequently operating the second belt means 3 and holding the first belt means 2 in the stationary position. In this case, after the rolling means 4 have been removed, the  
20 second belt means 3 are capable to carry the products 100 not to be rolled, in a so-called "in bulk" mode.

It is important to notice how the use of connecting means 5, 6 enables to operate both belt means 2, 3 separately by using the same actuating means 10 in opposite rotary directions.

25 The main advantage of the present invention is to provide an outlet device being capable of moving the products thus providing both an outlet of the so-called "in bulk" type, and an outlet for wraps of the "rolled design" type, requiring only minimum, quick and easy adjustments.


Another object is to provide an outlet device being capable of operating at high speed  
30 with reliable and regular operation, and which is compact and small-sized.

CLAIMS

- 1) Outlet device for chocolates and the like (100) for a wrapping machine (50) provided with at least moving means (51) for each product (100), said device (1) being characterized in that it comprises:
- first belt means (2) to move the products (100) to be rolled and operated by actuating means (10), by means of first connecting means (5), connecting the belt means (2) to the actuating means (10), according to a first direction (A) of a rotary motion by said actuating means (10);
  - rolling means (4) facing the first belt means (2) and intended to roll the products (100) being moved by said first belt means (2);
  - second belt means (3) to move those products (100) that do not require being rolled and operated by actuating means (10) through second connecting means (6) according to the second direction (B) of rotation of said actuating means (10).
- 2) Device according to claim 1 characterized in that the rolling means (4) are detachable and interposed between the first (2) and second (3) belt means.
- 3) Device according to claim 1 characterized in that the first (5) and second (6) connecting means comprise respective idle wheels gripping in the first (A) and second (B) direction of rotation of the actuating means (10), respectively.
- 4) Device according to claim 1 characterized in that the first (5) and second (6) connecting means are of the electromagnetic type and are operated by supplying means of the actuating means (10).
- 5) Device according to claim 1 characterized in that the first (5) and second (6) connecting means are connected to actuating means (10) through driving means (7).
- 6) Device according to claim 5 characterized in that the driving means (7) comprise a closed loop flexible element or a gear chain.

- 7) Device according to claim 1 characterized in that the rolling means (4) comprise an elongated concave housing (8), complementary shaped relative to the products (100), which is intended to roll said products (100) being moved by the first belt means (2).
- 5
- 8) Device according to claim 1 characterized in that the first belt means (2) are placed above the second belt means (3).
- 9) Device according to claim 1 characterized in that it comprises extraction means (15) intended to take each single product (100) from the moving means (51) and carry it to the belt means (2, 3).
- 10
- 10) Device according to claim 9 characterized in that the extraction means (15) comprise a pusher (16) being provided with a shaped housing for the product (100) and operated by operating means (17).
- 15
- 11) Device according to claim 10 characterized in that the operating means (17) comprise a couple of levers (18, 19), at least one of which being motor-driven, connected to the pusher (16) to form an articulated quadrilateral.
- 20
- 12) Device according to claim 1 characterized in that the actuating means (10) consist of an electric motor.
- 13) Device according to claim 1 characterized in that the first belt means (2) comprise at least one endless timing belt, which is coated on the outside relative to the teeth with a layer of elastic material (13).
- 25
- 14) Device according to claim 1 characterized in that the second belt means (3) comprise at least one endless belt.
- 30
- 15) Device according to any of the preceding claim characterized in that it comprises calculation and control means to control the phase relationship thereof at least between the extraction means (15) and the moving means (51).


1/3



**FIG.1**

Best Available Copy


**FIG. 2**  
**Best Available Copy**





Best Available Copy

FIG.3



**A. CLASSIFICATION OF SUBJECT MATTER**

IPC 7 B65B25/00 B65B11/56 B65B59/04

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B65B A23G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 423 693 C (LAUENSTEIN & CO G M B H FA) 2 October 1926 (1926-10-02) the whole document -----	1,7

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*Z\* document member of the same patent family

Date of the actual completion of the international search

5 January 2005

Date of mailing of the international search report

13/01/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Grentzius, W

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 423693	C	02-10-1926	NONE

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**